

1. TABULAR DESCRIPTION

INITIAL APPROACH											
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/ TCH	Nav Spec
010	IF	DL901	–	–	+1	–	–	+2150	-425	–	RNP 1
020	TF	DL900	–	178(176.9)	+1	9.26	–	+1850	–	–	RNP 1
010	IF	DL902	–	–	+1	–	–	+2150	-425	–	RNP 1
020	TF	DL900	–	358(356.9)	+1	9.26	–	+1850	–	–	RNP 1

MISSED APPROACH											
010	CA	–	–	088(086.9)	+1	–	–	+1280	–	–	RNP 1
020	DF	DL401	–	–	+1	–	R	@1850	-410	–	RNP 1
030	HM	DL401	–	306(305.0)	+1	–	L	+1850	–	–	RNP 1

2. HOLDING PROCEDURES

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
DL401	306(305.0)	+1	1 ≤ FL140 1.5 > FL140	L	+1850	-425 ≤ FL140 -445 > FL140	RNP 1

3. WAYPOINT LIST

WAYPOINT/FIX	COORDINATES (WGS-84)	
DL902	11°39'31.5"N	108°09'55.9"E
DL901	11°49'33.3"N	108°09'22.6"E
DL900 – BRG 267.93° ILK LLZ/D11.11 ILK DME	11°44'32.4"N	108°09'39.3"E
DL912 – BRG 267.92° ILK LLZ/D5.87 ILK DME	11°44'49.5"N	108°14'59.8"E
DL932 – BRG 267.92° ILK LLZ/D1.75 ILK DME	11°45'02.9"N	108°19'11.5"E
RWY09	11°45'08.07"N	108°20'48.97"E
DL401	11°29'37.6"N	108°24'09.7"E
ILK GP/DME	11°45'10.0"N	108°20'58.0"E
ILK LLZ	11°45'14.3"N	108°22'45.7"E