

1. TABULAR DESCRIPTION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/ TCH	Nav Spec
010	IF	DL282	–	–	+1	–	–	+2150	-425	–	RNP APCH
020	TF	DL281	–	358(356.9)	+1	9.28	–	+2050	-390	–	RNP APCH
010	IF	DL283	–	–	+1	–	–	+2600	-425	–	RNP APCH
020	TF	DL281	–	178(177.0)	+1	11.12	–	+2050	-390	–	RNP APCH
010	IF	SOSPA	–	–	+1	–	–	+2600	–	–	RNP APCH
020	TF	DL281	–	223(222.5)	+1	10.43	–	+2050	-390	–	RNP APCH
010	IF	DL281	–	–	+1	–	–	+2050	-390	–	RNP APCH
020	TF	DL280	–	268(266.9)	+1	9.11	–	+1750	–	–	RNP APCH
030	TF	RWY27 (MAPT)	Y	268(267.0)	+1	12.66	–	@977	–	-3.5°/ 15.25	RNP APCH
040	CF	DL400	Y	268(266.9)	+1	–	–	–	–	–	RNP APCH
050	DF	DL401	–	–	+1	–	L	@1850	-425	–	RNP APCH
060	HM	DL401	–	021(020.0)	+1	–	R	+1850	–	–	RNP APCH

2. HOLDING PROCEDURES

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
SOSPA	223(222.0)	+1	1 ≤ FL140 1.5 > FL140	L	+2600	-410 ≤ FL140 -445 > FL140	RNP APCH
DL282	358(357.0)	+1	1 ≤ FL140 1.5 > FL140	R	+2150	-425 ≤ FL140 -445 > FL140	RNP APCH
DL283	178(177.0)	+1	1 ≤ FL140 1.5 > FL140	L	+2600	-390 ≤ FL140 -445 > FL140	RNP APCH
DL401	021(020.0)	+1	1 ≤ FL140 1.5 > FL140	R	+1850	-425 ≤ FL140 -445 > FL140	RNP APCH

3. WAYPOINT LIST

WPT ID	COORDINATES (WGS-84)	
SOSPA	11°50'02.0"N	108°38'27.0"E
DL282	11°40'50.0"N	108°34'51.0"E
DL283	11°51'53.0"N	108°34'15.0"E
DL281	11°45'51.6"N	108°34'34.4"E
DL280	11°45'35.7"N	108°29'33.8"E
RWY27	11°45'13.75"N	108°22'36.14"E
DL400	11°45'02.5"N	108°19'02.6"E
DL401	11°29'37.6"N	108°24'09.7"E