Procedure coding

1. RNP Z RWY 06

INITIAL APPROACH SEGMENT FROM DOTHA

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA	Nav Spec
1	IF	DOTHA	-	-	0	-	-	-1500 +1200	-	-	RNP APCH
2	TF	CT601	-	113 (112.5)	0	11.7	-	@750	-	-	RNP APCH

INITIAL APPROACH SEGMENT FROM XUTHO

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA	Nav Spec
1	IF	XUTHO	-	-	0	-	-	-1500 +1200	-	-	RNP APCH
2	TF	CT601	-	348 (347.6)	0	15.3	-	@750	-	-	RNP APCH

INITIAL APPROACH SEGMENT FROM CT603

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA	Nav Spec
1	IF	CT603	-	-	0	-	-	+1200	-	-	RNP APCH
2	TF	CT601	-	150 (150.0)	0	9.3	-	@750	-	-	RNP APCH

INITIAL APPROACH SEGMENT FROM CT602

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA	Nav Spec
1	IF	CT602	-	-	0	-	-	+1200	-	-	RNP APCH
2	TF	CT601	-	330 (330.0)	0	9.3	-	@750	-	-	RNP APCH

FROM INTERMEDIATE APPROACH SEGMENT

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA	Nav Spec
1	IF	CT601	-	-	0	-	-	@750	-	-	RNP APCH
2	TF	CT600	-	060 (060.0)	0	9.3	-	@600	-	-	RNP APCH
3	TF	RWY06 (MAPT)	Y	060 (060.0)	0	11.1	-	@18	-	-3.0/ 15.25	RNP APCH
4	CA	-	-	060 (060.0)	0	-	-	+300	-	-	RNP APCH
5	CF	GOTLO	-	188 (187.6)	0	-	R	@900	-	-	RNP APCH
6	HM	GOTLO	-	291 (291.0)	0	-	L	+900	-	-	RNP APCH

2. HOLDING PROCEDURES

Holding Fix	Inbound Course/Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
DOTHA	113 (113.0)	0	1 ≤ FL140 1.5 > FL140	R	+1200	-425 ≤ FL140 -445 > FL140	RNP APCH
XUTHO	348 (348.0)	0	1 ≤ FL140 1.5 > FL140	L	+1200	-425 ≤ FL140 -445 > FL140	RNP APCH
CT603	150 (150.0)	0	1 ≤ FL140 1.5 > FL140	R	+1200	-425 ≤ FL140 -445 > FL140	RNP APCH
CT602	330 (330.0)	0	1 ≤ FL140 1.5 > FL140	L	+1200	-425 ≤ FL140 -445 > FL140	RNP APCH
GOTLO	291 (291.0)	0	1 ≤ FL140 1.5 > FL140	L	+900	-425 ≤ FL140 -445 > FL140	RNP APCH