1. TABULAR DESCRIPTION

BACHU 3A DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
INITIAL CLIMB RWY 07L										
010	CF	TS812	–	070	+1	11.7	–	–	–	RNAV 1
INITIAL CLIMB RWY 07R										
010	CF	TS812	–	068	+1	10.5	–	–	–	RNAV 1
FROM TS812										
010	IF	TS812	–	–	+1	–	–	–	–	RNAV 1
020	TF	TS834	–	340 (339.0)	+1	18.5	–	+900	–	RNAV 1
030	TF	TS836	–	250 (249.0)	+1	18.5	–	–	–	RNAV 1
040	TF	TS858	–	234 (233.3)	+1	21.2	–	+2750	–	RNAV 1
050	TF	BACHU	–	237 (235.5)	+1	51.0	–	–	–	RNAV 1

KADUM 2A DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
INITIAL CLIMB RWY 07L										
010	CF	TS812	–	070	+1	11.7	–	–	–	RNAV 1
INITIAL CLIMB RWY 07R										
010	CF	TS812	–	068	+1	10.5	–	–	–	RNAV 1
FROM TS812										
010	IF	TS812	–	–	+1	–	–	–	–	RNAV 1
020	TF	KADUM	–	031 (030.4)	+1	63.3	–	–	–	RNAV 1

DOVIN TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	KADUM	–	–	+1	–	–	–	–	RNAV 1
020	TF	DOVIN	–	062 (061.5)	+1	130.0	–	–	–	RNAV 1

BIXEX TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	KADUM	–	–	+1	–	–	–	–	RNAV 1
020	TF	BIXEX	–	078 (076.9)	+1	120.9	–	–	–	RNAV 1

PTH TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	KADUM	–	–	+1	–	–	–	–	RNAV 1
020	TF	PTH	–	114 (113.1)	+1	120.4	–	–	–	RNAV 1