1. TABULAR DESCRIPTION

DAN 1Q ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	DAN	–	–	+1	–	–	–	–	RNP 1
020	TF	SADIN	–	182(181.2)	+1	107.66	–	–	–	RNP 1
030	TF	TORUT	–	182(181.2)	+1	71.14	–	+FL130	–	RNP 1
040	TF	PK716	–	182(181.2)	+1	24.32	–	–	–	RNP 1
050	TF	PK714	–	150(148.7)	+1	12.88	–	+2150	–	RNP 1

CQ 2Q ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	CQ	–	–	+1	–	–	–	–	RNP 1
020	TF	SALIB	–	206(205.3)	+1	121.98	–	+FL130	–	RNP 1
030	TF	PK716	–	198(197.2)	+1	22.88	–	–	–	RNP 1
040	TF	PK714	–	150(148.7)	+1	12.88	–	+2150	–	RNP 1

PATMA 1D ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	PATMA	–	–	+1	–	–	–	–	RNP 1
020	TF	SADAS	–	002(001.1)	+1	108.84	–	–	–	RNP 1
030	TF	TEDIG	–	002(001.2)	+1	30.28	–	+FL110	–	RNP 1
040	TF	PK717	–	002(001.2)	+1	25.11	–	–	–	RNP 1
050	TF	PK715	–	081(080.1)	+1	27.73	–	+2750	–	RNP 1
060	TF	PK713	–	081(080.3)	+1	13.52	–	+2150	–	RNP 1

BMT 1D ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	BMT	–	–	+1	–	–	–	–	RNP 1
020	TF	SADAS	–	337(336.3)	+1	79.01	–	–	–	RNP 1
030	TF	TEDIG	–	002(001.2)	+1	30.28	–	+FL110	–	RNP 1
040	TF	PK717	–	002(001.2)	+1	25.11	–	–	–	RNP 1
050	TF	PK715	–	081(080.1)	+1	27.73	–	+2750	–	RNP 1
060	TF	PK713	–	081(080.3)	+1	13.52	–	+2150	–	RNP 1

2. HOLDING PROCEDURES

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
TEDIG	002(001.0)	+1	1 ≤ FL140 1.5 > FL140	R	+FL110	-425 ≤ FL140 -445 > FL140	RNP 1
SALIB	206(205.3)	+1	1 ≤ FL140 1.5 > FL140	L	+FL130	-425 ≤ FL140 -445 > FL140	RNP 1