1. TABULAR DESCRIPTION

INITIAL APPROACH											
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/ TCH	Nav Spec
010	IF	GOMEP	–	–	+2	–	–	+1200	-370	–	RNAV 1
020	TF	NB611	–	023(020.6)	+2	11.12	–	+750	–	–	RNAV 1
010	IF	VILOX	–	–	+2	–	–	+1200	-370	–	RNAV 1
020	TF	NB611	–	195(193.5)	+2	11.13	–	+750	–	–	RNAV 1
010	IF	NB362	–	–	+2	–	–	+1200	-370	–	RNAV 1
020	TF	NB611	–	109(107.0)	+2	9.02	–	+750	–	–	RNAV 1
010	IF	NB368	–	–	+2	–	–	+1500	-370	–	RNAV 1
020	TF	NB611	–	076(074.4)	+2	20.60	–	+750	–	–	RNAV 1

MISSED APPROACH											
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/ TCH	Nav Spec
010	CA	–	–	109(107.0)	+2	–	–	+300	–	–	RNAV 1
020	DF	LATUS	–	–	+2	–	–	@1200	–	–	RNAV 1
030	HM	LATUS	–	306(304.0)	+2	–	R	+1200	–	–	RNAV 1

2. HOLDING PROCEDURE

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
LATUS	306(304.0)	+2	1 ≤ FL140 1.5 > FL140	R	+1200	425 ≤ FL140 445 > FL140	RNAV 1

3. WAYPOINT LIST

WAYPOINT/FIX	**COORDINATES (WGS-84)**	
GOMEP	21°10'37.7"N	105°35'15.4"E
VILOX	21°22'08.1"N	105°39'01.2"E
NB362	21°17'42.0"N	105°32'32.0"E
NB368	21°13'16.0"N	105°26'03.0"E
NB611 – BRG 289.14° NBA LLZ/D9.61 NBA DME	21°16'16.1"N	105°37'31.1"E
NB613 – BRG 289.14° NBA LLZ/D4.51 NBA DME	21°14'45.9"N	105°42'44.2"E
LATUS	21°13'34.0"N	106°18'58.0"E
RW11R	21°13'28.91"N	105°47'10.85"E
NBA GP/DME	21°13'29.7"N	105°47'22.3"E
NBA LLZ	21°12'49.3"N	105°49'28.0"E