STANDARD ARRIVAL CHART-INSTRUMENT (STAR) - ICAO

TRANSITION ALTITUDE
3050

DAK LAK/BUON MA THUOT DOM (VVBM)
RNP RWY 09
MEVON 2G, ENGIM 2G, NOBID 2G
ONEBI 3G, DOVIN 2G, PATMA 2G

1. TABULAR DESCRIPTION

MEVON 2G ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/ TCH	Nav Spec
010	IF	MEVON	–	–	+1	–	–	–	–	–	RNP 1
020	TF	HINTO	–	173(172.2)	+1	44.36	–	+3050	–	–	RNP 1
030	TF	BM612	–	230(229.2)	+1	28.30	–	+1850	–	–	RNP 1

ENGIM 2G ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/ TCH	Nav Spec
010	IF	ENGIM	–	–	+1	–	–	–	–	–	RNP 1
020	TF	HINTO	–	182(181.3)	+1	44.42	–	+3050	–	–	RNP 1
030	TF	BM612	–	230(229.2)	+1	28.30	–	+1850	–	–	RNP 1

NOBID 2G ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/ TCH	Nav Spec
010	IF	NOBID	–	–	+1	–	–	–	–	–	RNP 1
020	TF	DOBLU	–	207(206.3)	+1	59.54	–	–	–	–	RNP 1
030	TF	BM512	–	220(219.0)	+1	9.07	–	–	–	–	RNP 1
040	TF	BM511	–	272(271.0)	+1	21.40	–	+2750	–	–	RNP 1
050	TF	BM612	–	272(271.0)	+1	17.00	–	+1850	–	–	RNP 1

ONEBI 3G ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/ TCH	Nav Spec
010	IF	ONEBI	–	–	+1	–	–	–	–	–	RNP 1
020	TF	VULIN	–	339(337.8)	+1	54.88	–	+3050	–	–	RNP 1
030	TF	BM514	–	350(349.5)	+1	19.26	–	+2750	–	–	RNP 1
040	TF	BM513	–	272(271.0)	+1	8.50	–	+2300	–	–	RNP 1
050	TF	BM613	–	272(271.0)	+1	8.50	–	+1850	–	–	RNP 1

DOVIN 2G ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/ TCH	Nav Spec
010	IF	DOVIN	–	–	+1	–	–	–	–	–	RNP 1
020	TF	VULIN	–	002(001.1)	+1	53.14	–	+3050	–	–	RNP 1
030	TF	BM514	–	350(349.5)	+1	19.26	–	+2750	–	–	RNP 1
040	TF	BM513	–	272(271.0)	+1	8.50	–	+2300	–	–	RNP 1
050	TF	BM613	–	272(271.0)	+1	8.50	–	+1850	–	–	RNP 1