STANDARD DEPARTURE CHART - INSTRUMENT (SID) - ICAO

TRANSITION ALTITUDE
2750 m

AN GIANG/PHU QUOC INTL (VVPQ)
RNP RWY 28
TRUMI 2A, HOTUN 1C,
NUMDI 1C, OSOTA 1C, THILI 1C

1. TABULAR DESCRIPTION

TRUMI 2A DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	CF	PQ281	–	276(275.7)	+0.4	–	–	–	-430	–	RNP 1
020	TF	PQ282	–	186(185.7)	+0.4	13.0	L	+1500	-430	–	RNP 1
030	TF	PQ284	–	096(095.7)	+0.4	19.8	L	+2450	–	–	RNP 1
040	TF	TRUMI	–	096(095.7)	+0.4	30.7	–	+FL110	–	–	RNP 1

TUNPO 2A TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	IF	TRUMI	–	–	+0.4	–	–	+FL110	–	–	RNP 1
020	TF	TUNPO	–	081(080.6)	+0.4	29.4	L	–	–	–	RNP 1

RG 1B TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	IF	TRUMI	–	–	+0.4	–	–	+FL110	–	–	RNP 1
020	TF	SAMIX	–	127(127.1)	+0.4	27.4	–	–	–	–	RNP 1
030	TF	VILIT	–	101(100.8)	+0.4	43.6	–	–	–	–	RNP 1
040	TF	RG	–	053(053.0)	+0.4	30.0	–	–	–	–	RNP 1

HOTUN 1C DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	CF	PQ281	–	276(275.7)	+0.4	–	–	–	-460	–	RNP 1
020	TF	PQ282	–	186(185.7)	+0.4	13.0	L	+1500	–	–	RNP 1
030	TF	PQ286	–	145(144.4)	+0.4	19.7	L	+2450	–	–	RNP 1
040	TF	HOTUN	–	145(144.4)	+0.4	14.6	–	+FL100	–	–	RNP 1

ADBOP 1A TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	IF	HOTUN	–	–	+0.4	–	–	+FL100	–	–	RNP 1
020	TF	TOTRA	–	179(178.5)	+0.4	29.4	R	+FL140	–	–	RNP 1
030	TF	ADBOP	–	179(178.5)	+0.4	115.7	–	–	–	–	RNP 1

NUMDI 1C DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	CF	PQ281	–	276(275.7)	+0.4	–	–	–	–	–	RNP 1
020	TF	NUMDI	–	339(339.0)	+0.4	31.3	R	@2450	–	–	RNP 1