STANDARD ARRIVAL CHART - INSTRUMENT (STAR) - ICAO

TRANSITION ALTITUDE
2750 m

AN GIANG/PHU QUOC INTL (VVPQ)
RNP RWY 10
TRUMI 2B, HOTUN 1F, NUMDI 1F, OSOTA 1F, THILI 1B

1. TABULAR DESCRIPTION

TRUMI 2B ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	TRUMI	–	–	+0.4	–	–	+FL120	–	RNP 1
020	TF	PQ410	–	276(275.8)	+0.4	29.6	–	+2450	–	RNP 1
030	TF	PQ210	–	276(275.7)	+0.4	28.4	–	1500	–	RNP 1

TUNPO 2C TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	TUNPO	–	–	+0.4	–	–	–	–	RNP 1
020	TF	TRUMI	–	261(260.7)	+0.4	29.4	–	+FL120	–	RNP 1

HOTUN 1F ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	HOTUN	–	–	+0.4	–	–	+2750	–	RNP 1
020	TF	PQ610	–	317(316.2)	+0.4	13.4	–	+2450	–	RNP 1
030	TF	PQ210	–	317(316.2)	+0.4	26.3	–	1500	–	RNP 1

ADBOP 1H TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	ADBOP	–	–	+0.4	–	–	–	–	RNP 1
020	TF	TOTRA	–	359(358.5)	+0.4	115.7	–	–	–	RNP 1
030	TF	HOTUN	–	359(358.5)	+0.4	29.4	–	+2750	–	RNP 1

NUMDI 1F ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	NUMDI	–	–	+0.4	–	–	@2450	–	RNP 1
020	TF	PQ310	–	163(162.4)	+0.4	16.3	–	1500	–	RNP 1

OSOTA 1F ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	OSOTA	–	–	+0.4	–	–	-2150 +1850	–	RNP 1
020	TF	PQ310	–	241(240.6)	+0.4	55.6	–	1500	–	RNP 1