STANDARD DEPARTURE CHART - INSTRUMENT (SID) - ICAO

TRANSITION ALTITUDE
2750 m

HO CHI MINH/CON DAO DOM (VVCS)
RNP RWY 11

BODOD 1D, NIXIV 1D, VEPKI 1D

1. TABULAR DESCRIPTION

BODOD 1D DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	CA	–	–	109(109.4)	0	–	–	+150	–	3.8	RNP 1
020	CF	CS521	–	109(109.4)	0	–	–	–	–	3.8	RNP 1
030	TF	CS522	–	019(019.4)	0	11.14	–	–	-465	3.8	RNP 1
040	TF	ASAGO	–	007(007.2)	0	18.30	–	–	–	3.8	RNP 1
050	TF	BODOD	–	007(006.9)	0	75.67	–	+FL140	–	3.8	RNP 1

NIXIV 1D DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	CA	–	–	109(109.4)	0	–	–	+150	–	4.1	RNP 1
020	CF	CS521	–	109(109.4)	0	–	–	–	–	4.1	RNP 1
030	TF	CS522	–	019(019.4)	0	11.14	–	–	-465	4.1	RNP 1
040	TF	CS523	–	329(329.2)	0	18.31	–	+1500	–	4.1	RNP 1
050	TF	VUSON	–	329(329.0)	0	8.52	–	+1850	–	4.1	RNP 1
060	TF	NIXIV	–	001(000.7)	0	43.05	–	+2150	–	–	RNP 1

VEPKI 1D DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	CA	–	–	109(109.4)	0	–	–	+150	–	4.1	RNP 1
020	CF	CS521	–	109(109.4)	0	–	–	–	–	4.1	RNP 1
030	TF	CS522	–	019(019.4)	0	11.14	–	–	-465	4.1	RNP 1
040	TF	CS523	–	329(329.2)	0	18.31	–	+1500	–	4.1	RNP 1
050	TF	VUSON	–	329(329.0)	0	8.52	–	+1850	–	4.1	RNP 1
060	TF	VEPKI	–	292(291.9)	0	30.23	–	+FL100	–	4.0	RNP 1

2. WAYPOINT LIST

WAYPOINT ID	COORDINATES (WGS-84)	
BODOD	09°38'22"N	106°51'29"E
CS521	08°42'04"N	106°43'14"E
CS522	08°47'46"N	106°45'15"E
CS523	08°56'17"N	106°40'08"E
ASAGO	08°57'37"N	106°46'30"E
NIXIV	09°23'36"N	106°38'02"E
VEPKI	09°06'21"N	106°22'25"E
VUSON	09°00'15"N	106°37'44"E