STANDARD ARRIVAL CHART-INSTRUMENT (STAR) - ICAO

TRANSITION ALTITUDE
2750

AN GIANG/RACH GIA DOM (VVRG)
RNP RWY 26
POTIX 1L, TRN 1L,
DADEM 1L, KISAN 1L

1. TABULAR DESCRIPTION

POTIX 1L ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	POTIX	–	–	0	–	–	–	–	RNP 1
020	TF	AGOBI	–	240(240.2)	0	31.13	–	-1500 +1200	–	RNP 1

TRN 1L ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	TRN	–	–	0	–	–	–	–	RNP 1
020	TF	AGOBI	–	272(272.0)	0	36.77	–	-1500 +1200	–	RNP 1

DADEM 1L ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	DADEM	–	–	0	–	–	@FL110	–	RNP 1
020	TF	OMDES	–	186(185.7)	0	74.08	–	+2150	–	RNP 1
030	TF	RG613	–	141(141.0)	0	18.86	–	+1200	–	RNP 1

KISAN 1L ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	KISAN	–	–	0	–	–	@FL110	–	RNP 1
020	TF	NISUM	–	142(141.9)	0	51.40	–	+2150	–	RNP 1
030	TF	RG613	–	104(104.2)	0	34.42	–	+1200	–	RNP 1

2. HOLDING PROCEDURES

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
AGOBI	218(218.0)	0	1 ≤ FL140 1.5 > FL140	R	+1200	-425 ≤ FL140 -445 > FL140	RNP 1
OMDES	141(141.0)	0	1 ≤ FL140 1.5 > FL140	R	+2150	-425 ≤ FL140 -445 > FL140	RNP 1
NISUM	104(104.0)	0	1 ≤ FL140 1.5 > FL140	R	+2150	-425 ≤ FL140 -445 > FL140	RNP 1

3. WAYPOINT LIST

WAYPOINT ID	COORDINATES (WGS-84)	
AGOBI	10°05'41"N	105°22'13"E
DADEM	10°53'44"N	105°13'41"E
KISAN	10°32'20"N	104°40'30"E
NISUM	10°10'23"N	104°57'52"E
OMDES	10°13'45"N	105°09'38"E
POTIX	10°14'05"N	105°37'00"E
RG613	10°05'48"N	105°16'08"E
TRN	10°05'00"N	105°42'20"E