1. TABULAR DESCRIPTION

HABAN 2E DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	CF	VH117	–	174(172.6)	+1	–	–	–	–	6.4	RNP 1
020	TF	VH417	–	127(126.2)	+1	9.9	–	+1200	–	6.4	RNP 1
030	TF	HABAN	–	127(126.2)	+1	12.8	–	@1850	–	5.1	RNP 1

KAMSU 1E TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	IF	HABAN	–	–	+1	–	–	@1850	–	–	RNP 1
020	TF	KAMSU	–	141(139.8)	+1	38.8	–	@2750	–	–	RNP 1

CAURO 2E DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	CF	VH117	–	174(172.6)	+1	–	–	–	–	6.0	RNP 1
020	TF	VH317	–	264(262.6)	+1	9.3	–	–	-370	6.0	RNP 1
030	TF	CAURO	–	293(292.2)	+1	23.8	–	+2450	–	6.0	RNP 1

IDOTA 1E TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	IF	CAURO	–	–	+1	–	–	+2450	–	–	RNP 1
020	TF	IDOTA	–	266(265.3)	+1	26.3	–	+FL130	–	5.8	RNP 1

MIBOS 2E DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	CF	VH117	–	174(172.6)	+1	–	–	–	–	6.9	RNP 1
020	TF	VH317	–	264(262.6)	+1	9.3	–	–	-370	6.9	RNP 1
030	TF	VH517	–	354(352.6)	+1	19.6	–	+2450	–	6.9	RNP 1
040	TF	MIBOS	–	354(352.6)	+1	18.7	–	+FL110	–	4.9	RNP 1

NAH 1E TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	IF	MIBOS	–	–	+1	–	–	+FL110	–	–	RNP 1
020	TF	TEBIR	–	034(033.3)	+1	57.6	–	–	–	–	RNP 1
030	TF	NAH	–	015(014.4)	+1	111.8	–	–	–	–	RNP 1