1. TABULAR DESCRIPTION

INITIAL APPROACH

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/ TCH	Nav Spec
010	IF	GOMEP	–	–	+2	–	–	+1200	-370	–	RNAV 1
020	TF	NB601	–	023(020.6)	+2	11.37	–	+750	–	–	RNAV 1
010	IF	VILOX	–	–	+2	–	–	+1200	-370	–	RNAV 1
020	TF	NB601	–	195(193.3)	+2	10.89	–	+750	–	–	RNAV 1
010	IF	NB362	–	–	+2	–	–	+1200	-370	–	RNAV 1
020	TF	NB601	–	107(105.4)	+2	9.04	–	+750	–	–	RNAV 1
010	IF	NB368	–	–	+2	–	–	+1500	-370	–	RNAV 1
020	TF	NB601	–	076(073.8)	+2	20.75	–	+750	–	–	RNAV 1

MISSED APPROACH

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/ TCH	Nav Spec
010	CA	–	–	109(107.0)	+2	–	–	+300	–	–	RNAV 1
020	DF	LATUS	–	–	+2	–	–	@1200	–	–	RNAV 1
030	HM	LATUS	–	306(304.0)	+2	–	R	+1200	–	–	RNAV 1

2. HOLDING PROCEDURE

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
LATUS	306(304.0)	+2	1 ≤ FL140 1.5 > FL140	R	+1200	-425 ≤ FL140 -445 > FL140	RNAV 1

3. WAYPOINT LIST

WAYPOINT/FIX	COORDINATES (WGS-84)	
GOMEP	21°10'37.7"N	105°35'15.4"E
VILOX	21°22'08.1"N	105°39'01.2"E
NB362	21°17'42.0"N	105°32'32.0"E
NB368	21°13'16.0"N	105°26'03.0"E
NB601 – BRG 289.14° NB LLZ/D9.93 NB DME	21°16'23.7"N	105°37'34.2"E
NB603 – BRG 289.14° NB LLZ/D4.51 NB DME	21°14'47.8"N	105°43'07.1"E
LATUS	21°13'34.0"N	106°18'58.0"E
RW11L	21°13'30.95"N	105°47'33.25"E
NB GP/DME	21°13'31.3"N	105°47'44.9"E
NB LLZ	21°12'56.3"N	105°49'33.2"E