| LEGEND | | |
|---|---|---|
| CONTROL AREA | CTR | |
| REPORTING POINT | (ON REQUEST) | △ |
| REPORTING POINT | (COMPULSORY) | ▲ |
| ATS ROUTE | | B468 |
| DIST IN KILOMETRES | | 30 |
| LOWER LIMIT | | FL200 |
| MAGNETIC BEARING | | 182° |

## RADIO NAVIGATION AID

| | |
|---|---|
| NAME | DIEN BIEN |
| NAVAID TYPE AND FREQUENCY | VOR/DME 113.6 |
| IDENTIFICATION | DBN |
| COORDINATES | 21°22'25"N 103°00'28"E |
| ELEVATION OF DME ANTENNA | 480 m |

### AREA MINIMUM ALTITUDE (AMA)

EACH 1° QUADRILATERAL CONTAINS AN AREA MINIMUM ALTITUDE (AMA) WHICH REPRESENTS THE LOWEST ALTITUDE WHICH MAY BE USED UNDER INSTRUMENT METEOROLOGICAL CONDITIONS (IMC). THE AMA PROVIDES A MINIMUM CLEARANCE OF 300 METRES (600M IN MOUNTAINOUS AREAS) ABOVE ALL OBSTACLES IN THE QUADRILATERAL. IT IS REPRESENTED IN THOUSANDS AND TENS OF METRES ABOVE MEAN SEA LEVEL (MSL).

EXAMPLE: 3 170 METRES $3_{17}$

CHANGE: AMA.

HANOI FIR (VIET NAM)

VIENTIANE FIR (LAOS)

DIEN BIEN TWR 118.7

P1 21°41'03"N 102°59'23"E

P2 21°37'50"N 103°18'11"E

P3 21°30'33"N 103°24'28"E

P4 20°57'35"N 103°12'03"E

P5 20°57'35"N 103°05'05"E

BEKLI 21°18'08"N 103°28'36"E

GUPET 21°09'00"N 103°24'17"E

LADON 21°06'13"N 102°58'01"E

DIEN BIEN NDB 380 DB 21°23'54"N 103°00'24"E

CTR DIEN BIEN FL135 GND/WATER 118.7

DIEN BIEN VOR/DME 113.6 DBN 21°22'25"N 103°00'28"E 480 m

B468 FL090

B468 30 FL200

B214 FL270

W4 49 FL130

101° 190° 010° 281°

$2_{66}$ $3_{17}$ $2_{96}$

2186 2021

ELEV, ALT IN METRES
DIST IN KILOMETRES
BRG ARE MAG VAR 2° W

SCALE 1 : 600 000

KILOMETRES 1 0 1 5

NM 1 0 1 2 3 4 5

CONTOUR INTERVALS 1700 1200 700