LEGEND

CONTROL ZONE (CTR)	----------
REPORTING POINT (COMPULSORY)	▲
DEPARTURE/ARRIVAL ROUTING	M510
DISTANCE IN KILOMETRES	30
MINIMUM FLIGHT ALTITUDE	FL040
TRANSITIONAL ROUTE	– – – –
MAGNETIC BEARING	150°

RADIO NAVIGATION AID

NAME	CANTHO
NAVAID TYPE AND FREQUENCY	DVOR/DME 113.2
IDENTIFICATION	TRN
COORDINATES	10°05'00"N 105°42'20"E

AREA MINIMUM ALTITUDE (AMA)

EACH 1° QUADRILATERAL CONTAINS AN AREA MINIMUM ALTITUDE (AMA) WHICH REPRESENTS THE LOWEST ALTITUDE WHICH MAY BE USED UNDER INSTRUMENT METEOROLOGICAL CONDITIONS (IMC). THE AMA PROVIDES A MINIMUM CLEARANCE OF 300 METRES (600M IN MOUNTAINOUS AREAS) ABOVE ALL OBSTACLES IN THE QUADRILATERAL. IT IS REPRESENTED IN THOUSANDS AND TENS OF METRES ABOVE MEAN SEA LEVEL (MSL).

EXAMPLE: 1070 METRES 107

CHANGE: AMA.

ELEV, ALT, HGT IN METRES
DIST IN KM
BRG ARE MAG
VAR 0°

CAN THO TWR: 118.8

HAU GIANG RIVER

CANTO 10°19'06"N 105°34'07"E

30 KM FM ARP

CHUTA 10°17'00"N 105°53'26"E

VINLO 10°15'05"N 105°55'13"E

POTIX 10°14'05"N 105°37'00"E

CANTHO DVOR/DME 113.2 TRN 10°05'00"N 105°42'20"E

DOTHA 10°01'32"N 105°26'17"E

GIANA 09°51'32"N 105°51'32"E

XUTHO 09°50'59"N 105°34'00"E

ANHOA 09°47'14"N 105°54'30"E

CTR CANTHO 2100M GND/WATER 118.8

107 080 055 055

SCALE 1 : 500 000

105°30'E 105°45'E 106°00'E

10° 05' N 10° 00' N 09° 45' N