TAKE-OFF MINIMA FOR RWY 17/35

RWY	ACFT CAT	RVR (M) or VIS (M)
17	A, B, C, D	800/1 000
35	A, B, C, D	600/900

LANDING MINIMA FOR RWY 17/35

VOR/DME approach procedures

Procedures	ACFT CAT	MDH (M)	With APCH LGT serviceable		With APCH LGT unserviceable	
			RVR (M)	VIS (M)	RVR (M)	VIS (M)
VOR Z, Y RWY 17	A, B, C, D	135	-	2 200	-	2 600

ILS approach procedures

Procedures	ACFT CAT	MDH/DH (M)	With APCH LGT serviceable		With APCH LGT unserviceable	
			RVR (M)	VIS (M)	RVR (M)	VIS (M)
ILS Z, V, U, X, W RWY 17	A, B, C, D	-/85	900	1 200	1 300	1 600
ILS Z, V, U, X, W GP INOP RWY 17	A, B, C, D	135/-	-	2 200	-	2 600

Note: Use VIS values only when RVR values are unavailable or the RVR system is out of service.

RNP approach procedures

Procedures	ACFT CAT	MDH (M)	With APCH LGT serviceable		With APCH LGT unserviceable	
			RVR (M)	VIS (M)	RVR (M)	VIS (M)
RNP Z Y LNAV/VNAV RWY 17	A, B, C, D	100	1 100	1 200	1 500	1 800
RNP Z Y LNAV RWY 17	A, B, C, D	130	-	2 000	-	2 400
RNP Z Y LNAV/VNAV RWY 35	A, B, C, D	100	-	-	1 500	1 800
RNP Z Y LNAV RWY 35	A, B, C, D	190	-	-	-	3 500

Note: Use VIS values only when RVR values are unavailable or the RVR system is out of service.

Circling procedures

	ACFT CAT	MDH (M)	With APCH LGT serviceable	
			RVR (M)	VIS (M)
Circling RWY 17/35	A, B	205	-	3 100
	C, D	425	-	4 400