Procedure coding

1. ADMAM ONE ALPHA DEPARTURE (ADMAM 1A)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)		Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	CI225	-	254	(252.3)	+1.5	-	-	-	-	5.5	RNAV 1
2	TF	ADMAM	-	304	(302.7)	+1.5	16.6	-	@1850	-	5.5	RNAV 1

NOB 1A TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)		Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	IF	ADMAM	-	-		+1.5	-	-	@1850	-	-	RNAV 1
2	TF	NOB	-	304	(302.6)	+1.5	74.3	-	-	-	-	RNAV 1

2. DOKLA ONE ALPHA DEPARTURE (DOKLA 1A)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)		Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	CI225	-	254	(252.3)	+1.5	-	-	-	-430	3.7	RNAV 1
2	TF	DOKLA	-	358	(356.5)	+1.5	33.1	-	@1850	-	3.7	RNAV 1

NAKHA 1B TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)		Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	IF	DOKLA	-	-		+1.5	-	-	@1850	-	-	RNAV 1
2	TF	NAKHA	-	358	(356.5)	+1.5	99.5	-	+FL110	-	-	RNAV 1

3. VANUC ONE CHARLIE DEPARTURE (VANUC 1C)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)		Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	CI125	-	254	(252.3)	+1.5	-	-	-	-430	4.9	RNAV 1
2	TF	CI325	-	170	(168.0)	+1.5	13.4	-	+1200	-	4.9	RNAV 1
3	TF	VANUC	-	152	(150.8)	+1.5	15.1	-	@1850	-	-	RNAV 1

Note: PDG 4.6% until reaching 100 m.

VIDAD 1A TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)		Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	IF	VANUC	-	-		+1.5	-	-	@1850	-	-	RNAV 1
2	TF	DOTUK	-	152	(150.8)	+1.5	45.2	-	-	-	-	RNAV 1
3	TF	VIDAD	-	184	(182.5)	+1.5	149.1	-	-	-	-	RNAV 1

4. VIBAO ONE ECHO DEPARTURE (VIBAO 1E)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)		Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	CI125	-	254	(252.3)	+1.5	-	-	-	-	3.8	RNAV 1
2	TF	VIBAO	-	224	(222.4)	+1.5	19.8	-	-1850 +1200	-	3.8	RNAV 1