TAKE–OFF MINIMA FOR RWY 06/24

RWY	ACFT CAT	RVR (M)	Visibility (M)
06/24	A, B, C, D		600

Note:

1. Take-off alternate aerodromes:
- *For international flights: Tan Son Nhat, Phu Quoc.*
- *For domestic flights: Tan Son Nhat, Phu Quoc,.*

2. When the ACFT can not choose any take-off alternate aerodromes as mentioned above, the landing minima as indicated in the below table will be applied to take-off minima.

LANDING MINIMA FOR RWY 06/24

1. VOR approach procedures

	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
VOR approach procedure for RWY 06	A, B	135		1 500
	C, D	135		1 700

	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
VOR approach procedure for RWY 24	A, B	135		1 800
	C, D	135		2 000

2. ILS approach procedures

	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
ILS approach procedure for RWY 06	A, B	60	550	800
	C, D	65	550	800

	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
ILS approach procedure for RWY 06 in case of GP unserviceable	A, B, C, D	135		1 700

	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
ILS Y, ILS X approach procedures for RWY 06	A, B	60	550	800
	C, D	65	550	800

	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
ILS Y, ILS X approach procedures for RWY 06 in case of GP unserviceable	A, B, C, D	140		1 800