STANDARD DEPARTURE CHART - INSTRUMENT (SID) - ICAO

TRANSITION LVL FL190
TRANSITION ALT 5500 m

HO CHI MINH/TAN SON NHAT INTL (VVTS)
RNAV RWY 25L/R
ANTRI 2D, LANHI 2D

1. TABULAR DESCRIPTION

ANTRI 2D DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
INITIAL CLIMB RWY 25L										
010	CF	TS612	Y	250	+1	7.1	-	-	-445	RNAV 1
020	DF	TS626	-	-	+1	-	-	+1200	-	RNAV 1
INITIAL CLIMB RWY 25R										
010	CF	TS614	Y	250	+1	7.2	-	-	-445	RNAV 1
020	DF	TS626	-	-	+1	-	-	+1200	-	RNAV 1
FROM TS626										
010	IF	TS626	-	-	+1	-	-	+1200	-	RNAV 1
020	TF	TS628	-	070 (069.1)	+1	9.8	-	-2750	-	RNAV 1
030	TF	TS632	-	070 (069.1)	+1	14.8	-	+3050	-	RNAV 1
040	TF	TS814	-	053 (051.5)	+1	32.1	-	-	-	RNAV 1
050	TF	TS816	-	032 (031.3)	+1	17.2	-	-	-	RNAV 1
060	TF	ANTRI	-	032 (031.3)	+1	17.2	-	-	-	RNAV 1

DOVIN TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	ANTRI	-	-	+1	-	-	-	-	RNAV 1
020	TF	DOVIN	-	050 (048.6)	+1	126.6	-	-	-	RNAV 1

BIXEX TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	ANTRI	-	-	+1	-	-	-	-	RNAV 1
020	TF	BIXEX	-	065 (063.5)	+1	110.0	-	-	-	RNAV 1

PTH TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	ANTRI	-	-	+1	-	-	-	-	RNAV 1
020	TF	PTH	-	107 (105.7)	+1	94.9	-	-	-	RNAV 1

PATMA TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	ANTRI	-	-	+1	-	-	-	-	RNAV 1
020	TF	PATMA	-	027 (025.6)	+1	144.2	-	-	-	RNAV 1