STANDARD DEPARTURE CHART - INSTRUMENT (SID) - ICAO

TRANSITION LVL FL190
TRANSITION ALT 5500 m

HO CHI MINH/TAN SON NHAT INTL (VVTS)
RNAV RWY 25L/R
BACHU 2D, KADUM 2D, ENPAS 2D
XOBAV 2D, MISAN 2D, SAPEN 2D

1. TABULAR DESCRIPTION

BACHU 2D DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
INITIAL CLIMB RWY 25L										
010	CF	TS616	-	250	+1	11.7	-	-	-	RNAV 1
INITIAL CLIMB RWY 25R										
010	CF	TS616	-	248	+1	10.8	-	-	-	RNAV 1
FROM TS616										
010	IF	TS616	-	-	+1	-	-	-	-	RNAV 1
020	TF	TS618	-	250 (249.0)	+1	26.5	-	-3350	-	RNAV 1
030	TF	BACHU	-	252 (251.1)	+1	34.9	-	-	-	RNAV 1

KADUM 2D DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
INITIAL CLIMB RWY 25L										
010	CF	TS616	-	250	+1	11.7	-	-	-	RNAV 1
INITIAL CLIMB RWY 25R										
010	CF	TS616	-	248	+1	10.8	-	-	-	RNAV 1
FROM TS616										
010	IF	TS616	-	-	+1	-	-	-	-	RNAV 1
020	TF	TS636	-	340 (339.0)	+1	16.7	-	-	-	RNAV 1
030	TF	TS638	-	053 (052.1)	+1	14.2	-	-3350	-	RNAV 1
040	TF	TS686	-	053 (052.2)	+1	28.1	-	+3050	-	RNAV 1
050	TF	KADUM	-	053 (052.2)	+1	37.9	-	-	-	RNAV 1
DOVIN TRANSITION										
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	KADUM	-	-	+1	-	-	-	-	RNAV 1
020	TF	DOVIN	-	062 (061.5)	+1	130.0	-	-	-	RNAV 1
BIXEX TRANSITION										
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	KADUM	-	-	+1	-	-	-	-	RNAV 1
020	TF	BIXEX	-	078 (076.9)	+1	120.9	-	-	-	RNAV 1
PTH TRANSITION										
010	IF	KADUM	-	-	+1	-	-	-	-	RNAV 1
020	TF	PTH	-	114 (113.1)	+1	120.4	-	-	-	RNAV 1