STANDARD DEPARTURE CHART - INSTRUMENT (SID) - ICAO

TRANSITION LVL FL190
TRANSITION ALT 5500 m

HO CHI MINH/TAN SON NHAT INTL (VVTS)
RNAV RWY 25L/R
BACHU 2D, KADUM 2D, ENPAS 2D
XOBAV 2D, MISAN 2D, SAPEN 2D

PATMA TRANSITION										
010	IF	KADUM	-	-	+1	-	-	-	-	RNAV 1
020	TF	PATMA	-	038 (037.0)	+1	135.7	-	-	-	RNAV 1

ENPAS 2D DEPARTURE										
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
INITIAL CLIMB RWY 25L										
010	CF	TS616	-	250	+1	11.7	-	-	-	RNAV 1
INITIAL CLIMB RWY 25R										
010	CF	TS616	-	248	+1	10.8	-	-	-	RNAV 1
FROM TS616										
010	IF	TS616	-	-	+1	-	-	-	-	RNAV 1
020	TF	TS618	-	250 (249.0)	+1	26.5	-	-3350	-	RNAV 1
030	TF	ENPAS	-	215 (214.3)	+1	38.4	-	-	-	RNAV 1
ANHOA TRANSITION										
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	ENPAS	-	-	+1	-	-	-	-	RNAV 1
020	TF	ANHOA	-	199 (198.2)	+1	71.3	-	-	-	RNAV 1

XOBAV 2D DEPARTURE										
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
INITIAL CLIMB RWY 25L										
010	CF	TS616	-	250	+1	11.7	-	-	-	RNAV 1
INITIAL CLIMB RWY 25R										
010	CF	TS616	-	248	+1	10.8	-	-	-	RNAV 1
FROM TS616										
010	IF	TS616	-	-	+1	-	-	-	-	RNAV 1
020	TF	TS641	-	172 (171.2)	+1	27.8	-	-2750	-	RNAV 1
030	TF	TS642	-	172 (171.2)	+1	13.0	-	-3350	-	RNAV 1
040	TF	TS644	-	172 (171.3)	+1	21.9	-	-4250	-	RNAV 1
050	TF	XOBAV	-	165 (164.4)	+1	8.3	-	-	-	RNAV 1
NIXIV TRANSITION										
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	XOBAV	-	-	+1	-	-	-	-	RNAV 1
020	TF	NIXIV	-	182 (180.7)	+1	82.6	-	-	-	RNAV 1