STANDARD DEPARTURE CHART - INSTRUMENT (SID) - ICAO

TRANSITION LVL FL190
TRANSITION ALT 5500 m

HO CHI MINH/TAN SON NHAT INTL (VVTS)
RNAV RWY 25L/R
BACHU 2D, KADUM 2D, ENPAS 2D
XOBAV 2D, MISAN 2D, SAPEN 2D

MISAN 2D DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
INITIAL CLIMB RWY 25L										
010	CF	TS616	-	250	+1	11.7	-	-	-	RNAV 1
INITIAL CLIMB RWY 25R										
010	CF	TS616	-	248	+1	10.8	-	-	-	RNAV 1
FROM TS616										
010	IF	TS616	-	-	+1	-	-	-	-	RNAV 1
020	TF	TS618	-	250 (249.0)	+1	26.5	-	-3350	-	RNAV 1
030	TF	MISAN	-	232 (231.2)	+1	36.3	-	-	-	RNAV 1
TRN TRANSITION										
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	MISAN	-	-	+1	-	-	-	-	RNAV 1
020	TF	TRN	-	222 (220.7)	+1	57.9	-	-	-	RNAV 1

SAPEN 2D DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
INITIAL CLIMB RWY 25L										
010	CF	TS616	-	250	+1	11.7	-	-	-	RNAV 1
INITIAL CLIMB RWY 25R										
010	CF	TS616	-	248	+1	10.8	-	-	-	RNAV 1
FROM TS616										
010	IF	TS616	-	-	+1	-	-	-	-	RNAV 1
020	TF	SAPEN	-	307 (305.9)	+1	47.2	-	-4250	-	RNAV 1