STANDARD DEPARTURE CHART - INSTRUMENT (SID) - ICAO

TRANSITION LVL FL190
TRANSITION ALT 5500 m

HO CHI MINH/TAN SON NHAT INTL (VVTS)
RNAV RWY 25L/R
TANOS 2E

1. TABULAR DESCRIPTION

TANOS 2E DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
INITIAL CLIMB RWY 25L										
010	CF	TS616	-	250	+1	11.7	-	-	-	RNAV 1
INITIAL CLIMB RWY 25R										
010	CF	TS616	-	248	+1	10.8	-	-	-	RNAV 1
FROM TS616										
010	IF	TS616	-	-	+1	-	-	-	-	RNAV 1
020	TF	TS618	-	250 (249.0)	+1	26.5	-	-3350	-	RNAV 1
030	TF	TS622	-	253 (251.6)	+1	27.8	-	-	-	RNAV 1
040	TF	TS624	-	163 (161.5)	+1	22.2	-	-	-500	RNAV 1
050	TF	TS626	-	067 (066.1)	+1	59.9	-	-	-	RNAV 1
060	TF	TS628	-	070 (069.1)	+1	9.8	-	+FL200	-	RNAV 1
070	TF	TS632	-	070 (069.1)	+1	14.8	-	-	-	RNAV 1
080	TF	TANOS	-	091 (090.0)	+1	52.6	-	-	-	RNAV 1

DOVIN TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	TANOS	-	-	+1	-	-	-	-	RNAV 1
020	TF	DOVIN	-	034 (032.7)	+1	158.1	-	-	-	RNAV 1

BIXEX TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	TANOS	-	-	+1	-	-	-	-	RNAV 1
020	TF	BIXEX	-	043 (042.1)	+1	132.6	-	-	-	RNAV 1

PTH TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	TANOS	-	-	+1	-	-	-	-	RNAV 1
020	TF	PTH	-	075 (073.9)	+1	85.2	-	-	-	RNAV 1