1. TABULAR DESCRIPTION

INITIAL APPROACH

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/ TCH	Nav Spec
010	IF	HINTO	–	–	+1	–	–	+1500	–	–	RNP 1
020	TF	BM612	–	230(229.2)	+1	28.30	–	–	–	–	RNP 1
030	TF	BM611	–	182(181.0)	+1	11.11	–	@1350	–	–	RNP 1

MISSED APPROACH

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/ TCH	Nav Spec
010	CA	–	–	092(091.0)	+1	–	–	@750	–	–	RNP 1
020	DF	HINTO	–	–	+1	–	L	@1500	–	–	RNP 1
030	HM	HINTO	–	230(229.2)	+1	–	R	+1500	–	–	RNP 1

2. HOLDING PROCEDURES

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
HINTO	230(229.2)	+1	1 ≤ FL140 1.5 > FL140	R	+1500	-425 ≤ FL140 -445 > FL140	RNP 1

3. WAYPOINT LIST

WAYPOINT ID/FIX	**COORDINATES (WGS-84)**	
HINTO (IAF)	12°56'21.0"N	108°07'47.0"E
BM612	12°46'18.9"N	107°55'56.8"E
BM611 – BRG 271.99° IBM LLZ/D10.47 IBM DME (IF)	12°40'17.3"N	107°55'50.7"E
BM609 – BRG 271.97° IBM LLZ/D5.42 IBM DME (FAP/FAF)	12°40'12.1"N	108°01'00.2"E
THR RWY 09 – BRG 271.97° IBM LLZ/D0.16 IBM DME (MAPT)	12°40'06.80"N	108°06'23.30"E
IBM LLZ	12°40'05.0"N	108°08'10.3"E
IBM DME	12°40'04.2"N	108°06'32.9"E