

Procedure coding

1. RNP Y RWY 06

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA	Nav Spec
1	IF	GOTLO	-	-	0	-	-	+900	-	-	RNP APCH
2	TF	CT602	-	291 (291.0)	0	26.1	-	-	-	-	RNP APCH
3	TF	CT601	-	330 (330.0)	0	9.3	-	@750	-	-	RNP APCH
4	TF	CT600	-	060 (060.0)	0	9.3	-	@600	-	-	RNP APCH
5	TF	RWY06 (MAPT)	Y	060 (060.0)	0	11.1	-	@18	-	-3.0/ 15.25	RNP APCH
6	CA	-	-	060 (060.0)	0	-	-	+300	-	-	RNP APCH
7	CF	GOTLO	-	188 (187.6)	0	-	R	@900	-	-	RNP APCH
8	HM	GOTLO	-	291 (291.0)	0	-	L	+900	-	-	RNP APCH

2. HOLDING PROCEDURE

Holding Fix	Inbound Course/Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
GOTLO	291 (291.0)	0	1 ≤ FL140 1.5 > FL140	L	+900	-425 ≤ FL140 -445 > FL140	RNP APCH