

Procedure coding**1. RNP Z RWY 24****INITIAL APPROACH SEGMENT FROM CHUTA**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA	Nav Spec
1	IF	CHUTA	-	-	0	-	-	-1850 +1200	-	-	RNP APCH
2	TF	CT401	-	185 (184.7)	0	11.2	-	@750	-	-	RNP APCH

INITIAL APPROACH SEGMENT FROM VINLO

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA	Nav Spec
1	IF	VINLO	-	-	0	-	-	-1850 +1200	-	-	RNP APCH
2	TF	CT401	-	209 (208.7)	0	8.7	-	@750	-	-	RNP APCH

INITIAL APPROACH SEGMENT FROM CT402

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA	Nav Spec
1	IF	CT402	-	-	0	-	-	+1200	-	-	RNP APCH
2	TF	CT401	-	330 (330.0)	0	9.3	-	@750	-	-	RNP APCH

FROM INTERMEDIATE APPROACH SEGMENT

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA	Nav Spec
1	IF	CT401	-	-	0	-	-	@750	-	-	RNP APCH
2	TF	CT400	-	240 (240.0)	0	9.3	-	@600	-	-	RNP APCH
3	TF	MIGAV (MAPT)	Y	240 (240.0)	0	9.0	-	@130	-	-3.0/ 15.25	RNP APCH
4	CF	CT800	-	240 (240.0)	0	-	-	-	-	-	RNP APCH
5	TF	CT801	-	150 (150.0)	0	8.2	-	-	-390	-	RNP APCH
6	TF	CT802	-	104 (104.2)	0	22.3	-	@900	-	-	RNP APCH
7	HM	CT802	-	008 (008.4)	0	-	R	+900	-	-	RNP APCH

2. HOLDING PROCEDURES

Holding Fix	Inbound Course/Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
CHUTA	185 (184.7)	0	1 ≤ FL140 1.5 > FL140	L	+1200	-425 ≤ FL140 -445 > FL140	RNP APCH
VINLO	209 (208.7)	0	1 ≤ FL140 1.5 > FL140	L	+1200	-425 ≤ FL140 -445 > FL140	RNP APCH
CT402	330 (330.0)	0	1 ≤ FL140 1.5 > FL140	R	+1200	-425 ≤ FL140 -445 > FL140	RNP APCH
CT802	008 (008.4)	0	1 ≤ FL140 1.5 > FL140	R	+900	-425 ≤ FL140 -445 > FL140	RNP APCH