

AD OPERATING MINIMA

CAN THO WEATHER MNM
VVCT

TAKE-OFF MINIMA FOR RWY 06/24

RWY	ACFT CAT	RVR (M)	Visibility (M)
06/24	A, B, C, D		600

- Note:**
- Take-off alternate aerodromes:
 - For international flights: Tan Son Nhat, Phu Quoc.
 - For domestic flights: Tan Son Nhat, Phu Quoc, Rach Gia (CAT A, B, C).
 - When the ACFT can not choose any take-off alternate aerodromes as mentioned above, the landing minima as indicated in the below table will be applied to take-off minima.

LANDING MINIMA FOR RWY 06/24

1. VOR approach procedures

VOR approach procedure for RWY 06	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	135		1 500
	C, D	135		1 700

VOR approach procedure for RWY 24	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	135		1 800
	C, D	135		2 000

2. ILS approach procedures

ILS approach procedure for RWY 06	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	60	550	800
	C, D	65	550	800

ILS approach procedure for RWY 06 in case of GP unserviceable	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C, D	135		1 700

ILS Y, ILS X approach procedures for RWY 06	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	60	550	800
	C, D	65	550	800

ILS Y, ILS X approach procedures for RWY 06 in case of GP unserviceable	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C, D	140		1 800