

Procedure coding**1. RG ONE ECHO DEPARTURE (RG 1E)**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	CT611	-	060 (060.0)	0	-	-	-	-	5.6	RNP 1
2	TF	CT631	-	330 (330.0)	0	9.3	-	+900	-390	5.6	RNP 1
3	TF	CT632	-	240 (240.1)	0	10.1	-	-1500 +1200	-	-	RNP 1
4	TF	CT633	-	240 (240.0)	0	9.6	-	+1850	-	6.8	RNP 1
5	TF	DOTHA	-	240 (240.1)	0	20.2	-	-	-	-	RNP 1
6	TF	RG	-	258 (257.7)	0	34.2	-	-	-	-	RNP 1

2. QL ONE ECHO DEPARTURE (QL 1E)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	CT611	-	060 (060.0)	0	-	-	-	-	5.6	RNP 1
2	TF	CT631	-	330 (330.0)	0	9.3	-	+900	-390	5.6	RNP 1
3	TF	CT632	-	240 (240.1)	0	10.1	-	-1500 +1200	-	-	RNP 1
4	TF	CT633	-	240 (240.0)	0	9.6	-	+1850	-	6.8	RNP 1
5	TF	CT634	-	187 (186.7)	0	6.9	-	+2150	-	4.3	RNP 1
6	TF	XUTHO	-	187 (186.7)	0	22.8	-	-	-	-	RNP 1
7	TF	QL	-	210 (209.9)	0	85.9	-	-	-	-	RNP 1

3. BIBAN ONE ECHO DEPARTURE (BIBAN 1E)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	CT611	-	060 (060.0)	0	-	-	-	-390	6.2	RNP 1
2	TF	CT621	-	150 (150.0)	0	16.5	-	@1500	-	6.2	RNP 1
3	TF	BAXEL	-	150 (150.0)	0	11.5	-	+2150	-	5.7	RNP 1
4	TF	ANHOA	-	187 (186.7)	0	14.2	-	-	-	-	RNP 1
5	TF	BIBAN	-	215 (215.1)	0	173.9	-	+FL135	-	-	RNP 1

4. VEPKI ONE JULIETT DEPARTURE (VEPKI 1J)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	CT611	-	060 (060.0)	0	-	-	-	-390	6.2	RNP 1
2	TF	CT621	-	150 (150.0)	0	16.5	-	@1500	-	6.2	RNP 1
3	TF	BAXEL	-	150 (150.0)	0	11.5	-	+2150	-	5.7	RNP 1
4	TF	ANHOA	-	187 (186.7)	0	14.2	-	-	-	-	RNP 1
5	TF	VEPKI	-	146 (145.8)	0	91.1	-	+FL100	-	-	RNP 1