
Procedure coding**1. DADEM ONE ECHO DEPARTURE (DADEM 1E)**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	CT611	-	060 (060.0)	0	-	-	-	-390	5.7	RNP 1
2	TF	CT651	-	330 (330.0)	0	14.7	-	-1500 +1200	-	5.7	RNP 1
3	TF	NILWA	-	330 (330.0)	0	13.3	-	-	-	-	RNP 1
4	TF	DADEM	-	321 (321.3)	0	77.0	-	+FL100	-	-	RNP 1

2. MOXEB ONE KILO DEPARTURE (MOXEB 1K)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	CT611	-	060 (060.0)	0	-	-	-	-390	5.7	RNP 1
2	TF	CT651	-	330 (330.0)	0	14.7	-	-1500 +1200	-	5.7	RNP 1
3	TF	NILWA	-	330 (330.0)	0	13.3	-	-	-	-	RNP 1
4	TF	LIBSU	-	061 (060.9)	0	73.2	-	-	-	-	RNP 1
5	TF	MOXEB	-	043 (042.6)	0	33.9	-	-	-	-	RNP 1

3. ENPAS ONE KILO DEPARTURE (ENPAS 1K)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	CT611	-	060 (060.0)	0	-	-	-	-390	5.7	RNP 1
2	TF	CT651	-	330 (330.0)	0	14.7	-	-1500 +1200	-	5.7	RNP 1
3	TF	NILWA	-	330 (330.0)	0	13.3	-	-	-	-	RNP 1
4	TF	ENPAS	-	084 (083.8)	0	48.8	-	-	-	-	RNP 1