

Procedure coding**1. MOXEB ONE FOXTROT DEPARTURE (MOXEB 1F)**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	CT411	-	240 (240.0)	0	-	-	-	-	7.0	RNP 1
2	TF	CT413	-	330 (330.0)	0	9.3	-	+1200	-390	7.0	RNP 1
3	TF	CT415	-	060 (060.1)	0	23.5	-	@2150	-	4.1	RNP 1
4	TF	CHUTA	-	060 (060.1)	0	15.7	-	-	-	-	RNP 1
5	TF	MOXEB	-	043 (042.5)	0	92.6	-	-	-	-	RNP 1

2. ENPAS ONE CHARLIE DEPARTURE (ENPAS 1C)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	CT411	-	240 (240.0)	0	-	-	-	-	7.0	RNP 1
2	TF	CT413	-	330 (330.0)	0	9.3	-	+1200	-390	7.0	RNP 1
3	TF	CT415	-	060 (060.1)	0	23.5	-	@2150	-	4.1	RNP 1
4	TF	VINLO	-	076 (075.7)	0	17.4	-	-	-	-	RNP 1
5	TF	ENPAS	-	052 (051.9)	0	26.6	-	-	-	-	RNP 1

3. DADEM ONE FOXTROT DEPARTURE (DADEM 1F)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	CT411	-	240 (240.0)	0	-	-	-	-	7.0	RNP 1
2	TF	CT413	-	330 (330.0)	0	9.3	-	+1200	-390	7.0	RNP 1
3	TF	NILWA	-	020 (019.5)	0	28.8	-	@2150	-	-	RNP 1
4	TF	DADEM	-	321 (321.3)	0	77.0	-	+FL100	-	-	RNP 1

4. MOXEB ONE LIMA DEPARTURE (MOXEB 1L)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	CT411	-	240 (240.0)	0	-	-	-	-	7.0	RNP 1
2	TF	CT413	-	330 (330.0)	0	9.3	-	+1200	-390	7.0	RNP 1
3	TF	NILWA	-	020 (019.5)	0	28.8	-	@2150	-	-	RNP 1
4	TF	LIBSU	-	061 (060.9)	0	73.2	-	-	-	-	RNP 1
5	TF	MOXEB	-	043 (042.6)	0	33.9	-	-	-	-	RNP 1

5. ENPAS ONE LIMA DEPARTURE (ENPAS 1L)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	CT411	-	240 (240.0)	0	-	-	-	-	7.0	RNP 1
2	TF	CT413	-	330 (330.0)	0	9.3	-	+1200	-390	7.0	RNP 1
3	TF	NILWA	-	020 (019.5)	0	28.8	-	@2150	-	-	RNP 1
4	TF	ENPAS	-	084 (083.8)	0	48.8	-	-	-	-	RNP 1