

Procedure coding**1. RG ONE FOXTROT DEPARTURE (RG 1F)**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	CT421	-	240 (240.0)	0	-	-	+900	-	6.5	RNP 1
2	TF	DOTHA	-	274 (274.5)	0	16.4	-	-2150 +1200	-	-	RNP 1
3	TF	RG	-	258 (257.7)	0	34.2	-	-	-	-	RNP 1

2. QL ONE FOXTROT DEPARTURE (QL 1F)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	CT421	-	240 (240.0)	0	-	-	+900	-	6.5	RNP 1
2	TF	XUTHO	-	187 (187.2)	0	18.3	-	-2150 +1200	-	-	RNP 1
3	TF	QL	-	210 (209.9)	0	85.9	-	-	-	-	RNP 1

3. BIBAN ONE FOXTROT DEPARTURE (BIBAN 1F)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	CT421	-	240 (240.0)	0	-	-	+900	-	6.5	RNP 1
2	TF	CT422	-	150 (150.0)	0	17.2	-	-	-	-	RNP 1
3	TF	CT423	-	111 (111.0)	0	7.7	-	-2150 +1500	-	-	RNP 1
4	TF	GOTLO	-	111 (111.0)	0	8.1	-	+2450	-	-	RNP 1
5	TF	ANHOA	-	111 (111.0)	0	12.6	-	-	-	-	RNP 1
6	TF	BIBAN	-	215 (215.1)	0	173.9	-	+FL135	-	-	RNP 1

4. VEPKI ONE KILO DEPARTURE (VEPKI 1K)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	CT421	-	240 (240.0)	0	-	-	+900	-	6.5	RNP 1
2	TF	CT422	-	150 (150.0)	0	17.2	-	-	-	-	RNP 1
3	TF	CT423	-	111 (111.0)	0	7.7	-	-2150 +1500	-	-	RNP 1
4	TF	GOTLO	-	111 (111.0)	0	8.1	-	+2450	-	-	RNP 1
5	TF	ANHOA	-	111 (111.0)	0	12.6	-	-	-	-	RNP 1
6	TF	VEPKI	-	146 (145.8)	0	91.1	-	+FL100	-	-	RNP 1